

AS3566 Australian Standard **BUILDING FASTENERS**



100% Made in Taiwan

ISO 9001:2015



















2009

Established in 2009 and began the trade of selling construction fasteners.

2014

In 2014, the 100% Made in Taiwan, BDN Fasteners brand nam stepped into the fasteners scene.

2015

BDN FASTENERS Thailand was established in 2015, and set up as a base for sales and promotion of BDN Fasteners in ASEAN countries. 2017

BDN Fasteners takes a major step forward and builds a new facility dedicated to Heading, Threading, and Pinch Pointing processes – maximizing speed and efficiency, taking our service and quality to 2018

Despite hard times, BDN Fasteners takes yet another bold step forwards, relocating to a larger storage and packaging facility for better logistics, accommodate additional personnel, and new packaging machinery.

PVT.LTD. was established in the end of July, 2018 for sales in Indian market.

2019

BDN FASTENERS takes another bold step forwards, moving our packaging and warehouse facility to a larger area in order to provide better, faster service in the near future 2022

Despite the outburst of COVID-19 and the world going topsy-turvy, BDN Fasteners has taken advantage of the calm within the storm, expanding of our facility and adding multiple collated screw assembly lines, fully prepared once the global economy bounces back to pre-pandemic levels.



CONTENTS



METAL-Tite™ Self-Drilling Screws ·····							
Fixing Cladding to Metal	BN 3		5				
Fixing to Thick Steel (No.5 Drill Point)	(BN)		6				
Crest Fixing Fasteners (Full Thread)	(BN)		7				
Crest Fixing Fasteners (Double Thread)	(BN)		8				
Stitching Fasteners (Reduced Point)	BN		9				
Stitching Fasteners (Needle Point)	BN 3	111111111	10				
Concealed Fixing Fasteners	BIN		11				
Clip-Fix Button Head Self-Drilling Screws	(B) N		12				
Framing Screws							
Truss to Plate Connection	BN3		13				
TRUSS-Tite™ Fixing Steel Roof and Floor Trusses	(BN)		14				
FRAME-Tite™ Fixing to Steel Wall Frames	B N		15				
POLYXPAND™							
Fixing Polycarbonate Sheeting to Metal	BN 3		16				
POLY-FAST™ Polycarbonate Roof Fasteners							
POLY-FAST™ Metal	BN 4		17				
POLY-FAST™ Timber	BN 4	- Sight	18				
POLY-FAST™ Duo	(BN 3						
Collated Screws			20				
TIMBER-Tite™ Type 17 Self-Tapping Screws	·						
Valley Fixing Fasteners	BN 3		21				
Fixing Roof Sheeting to Timber (Double Thread)	(BN)		22				

Product Overview - BDN Fasteners®

Coating Type: Zinc + Organic Coating (Ruspert)
SGS Certification: SST 1000 hrs + Kesternich 7 cycles

Туре	BN 3	BN 3	(B) 3	BN 3	BN 3	(BN 3)	BN 3	F	
Product									
Application									
Max. drilling capacity [mm]	4.0mm thick (For #10 gauge)	6.0mm thick (For #12 gauge)	12.5mm thick	6.0mm thick	6.0mm thick	1+1mm thick	1+1mm thick	4.0mm thick	2.5mm thick
Gauge TPI x Length [mm]	10-16 x 16 10-16 x 19 10-16 x 25	12-14 x 20 12-14 x 25 12-14 x 30 12-14 x 35	12-24 × 32 12-24 × 38 12-24 × 50	12-14 x 50 12-14 x 55 12-14 x 65 12-14 x 75 12-14 x 85 12-14 x 110 12-14 x 130	12-14 x 45 12-14 x 55 12-14 x 65 12-14 x 75 12-14 x 90	15-15 x 20	10-16 x 19	10-24 x 16 10-24 x 22	8-18 x 45 8-18 x 65
Product webpage QR code	■21 234 7 1	900 500 500 500					74 E		







B N	BNS	BN 3	BN ₃	BN 3	BN B	BN 4	BN BN 4	BN 3	Туре
									Product
•									Application
4.0mm thick	1.5 + 1.5mm thick	0.75mm to 1.6mm thick	Min 20mm Timber penetration	Min 25mm Timber penetration	5.5mm thick	4.5mm thick	Min 25mm Timber penetration	3mm thick	Max. drilling capacity [mm]
M6.0-1.00 x 22	12-14 x 20	M8.0-2.12 x 16	10-12 x 20	12-11 x 50 12-11 x 65 12-11 x 75	12-14 x 40 (Valleys) 12-14 x 55 12-14 x 65 12-14 x 72 (Crests)	12-14 x 60	12-11 x 50	12-11 x 50	Gauge TPI x Length [mm]
									Product webpage QR code



BN3 METAL-Tite™ Dual-Edge® Self-Drilling Screws


Fixing Cladding to Metal





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. 4.0mm thick (For #10 gauge) Max. 6.0mm thick (For #12 gauge)

PRODUCT FEATURES

Hex Washer Flange Dual-Edge® Drill Point

WASHER

Eco-BDN® Green Washer





PART NUMBER



#10 Gauge

SDHC1016C3N 10-16 x 16mm SDHC1019C3N 10-16 x 19mm SDHC1025C3N 10-16 x 25mm




#12 Gauge


SDHC1220C3N 12-14 x 20mm SDHC1225C3N 12-14 x 25mm SDHC1230C3N 12-14 x 30mm SDHC1235C3N 12-14 x 35mm



BN3 METAL-Tite™ Heavy Duty Self-Drilling Screws


Fixing to Thick Steel - No. 5 Drill Point





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. 12.5mm thick

PRODUCT FEATURES

Hex Washer Flange Thread slot No.5 Drilling Point

WASHER

Eco-BDN® Green Washer





PART NUMBER


#12 Gauge


SDH5F1232C3N 12-24 x 32mm SDH5F1238C3N 12-24 x 38mm SDH5F1250C3N 12-24 x 50mm



BN3 METAL-Tite™ Dual-Edge® Self-Drilling Screws


Fixing Roof Sheeting to Metal - Full Thread





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. 6.0mm thick (For #12 gauge)


PRODUCT FEATURES

Hex Washer Flange Full Thread Dual-Edge® Drill Point

WASHER

Eco-BDN® Green Washer





PART NUMBER

#12 Gauge

 SDHC1245C3N
 12-14 x 45mm
 SDHC1275C3N
 12-14 x 75mm

 SDHC1255C3N
 12-14 x 55mm
 SDHC1290C3N
 12-14 x 90mm


SST 1000 hrs + Kesternich 7 cycles


SDHC1265C3N 12-14 x 65mm



BN3 METAL-Tite™ Dual-Edge® Self-Drilling Screws


Fixing Roof Sheeting to Metal - Double Thread





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. 6.0mm thick (For #12 gauge)

PRODUCT FEATURES

Hex Washer Flange
Dual-Edge® Drill Point
Double Thread
Scratshank

WASHER

Eco-BDN® Green Washer





PART NUMBER

#12 Gauge

 SDHCG1250C3N
 12-14 x 50mm
 SDHCG1285C3N
 12-14 x 85mm

 SDHCG1255C3N
 12-14 x 55mm
 SDHCG12110C3N
 12-14 x 110mm


 SDHCG1265C3N
 12-14 x 65mm
 SDHCG12130C3N
 12-14 x 130mm


 SDHCG1275C3N
 12-14 x 75mm



BN3 METAL-Tite™ Stitching Fasteners


Stitching Fasteners - Reduced Point





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. drilling capacity 1+1mm thick

PRODUCT FEATURES

Hex Washer Flange Thunder-Shot Reduced Point Harpoon Thread

WASHER

Eco-BDN® Green Washer





PART NUMBER


#15 Gauge


SDHC1520C3N 15-15 x 20mm



BN3 METAL-Tite™ Stitching Fasteners


Stitching Fasteners - Needle Point





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. drilling capacity 1+1mm thick

PRODUCT FEATURES

Hex Washer Flange Needle Point

WASHER

Eco-BDN® Green Washer





PART NUMBER


#10 Gauge


SDHST1019C3N 10-16x19mm



BN3 METAL-Tite™ Concealed Fixing Fasteners


Fixing steel sheets into steel substrates





ADAPTER TO USE

Philips Bit (PH2+)



STEEL PENETRATION

Max. 4.0mm thick

PRODUCT FEATURES

Wafer Head Philips Drive Thunder-Shot Point

PART NUMBER


#10 Gauge

SDWF1016C3 10-24 x 16mm SDWF1022C3 10-24 x 22mm




BN3 Clip-Fix Button Head Self-Drilling Screws

BDN Clip-Fix button head self-drilling screws is suited for concealed and pierce fixing snap-lock type cladding system panels to thin gauge steel battens. Clip-Fix's low-profile button head are concealed and will not interfere when panels are snapped into position, providing a clean finish.



ADAPTER TO USE

Philips Bit (PH2+)



STEEL PENETRATION

Max. 2.5mm thick

PRODUCT FEATURES

Low profile Button head Philips Drive Thunder-Shot Drilling Point Suited for clip fixing to batten supports

PART NUMBER


#8 Gauge


BN3-SDBT0845C3 8-18 x 45mm BN3-SDBT0865C3 8-18 x 65mm



BN3 METAL-Tite™ Truss to Plate Connection Fasteners


Truss to Plate Connecting Fasteners





ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. drilling capacity 1.5+1.5mm thick

PRODUCT FEATURES

Dual-Edge® Drill Point High pull-out strength


PART NUMBER

SDHCF1220C3 12-14 x 20mm




BN3 METAL-Tite™ Framing Fasteners

Fixing Steel Roof and Floor Trusses



ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

From 0.75mm to 1.6mm thick

PRODUCT FEATURES

- Superior holding strength
- Self space tapping point makes it easy to start and align in the punched hole
- Easy application


PART NUMBER

SDHTSF0816C3 M8.0-2.12x16mm




BN3 FRAME-Tite™ Framing Fasteners

Fixing to steel wall frames



ADAPTER TO USE

Philips Bit (PH3+)



STEEL PENETRATION

Max. 4.0mm thick

PRODUCT FEATURES

- Smooth flat top head for discreet fixing
- Superior holding strength
- Easy application


PART NUMBER

SDFHSF0622C3 M6.0-1.00 x 22mm




BN3 POLYXPAND™ Plastic Skylight Fixing Fasteners

Fixing Polycarbonate Sheeting to Metal



ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max 5.5mm Thick

PRODUCT FEATURES

Hex Washer Flange Expansion Wings Thunder-Shot Point

WASHER


Ø 25mm Dome Grey EPDM



PART NUMBER

#12 Gauge

SDHCP1240C3D 12-14 x 40mm SDHCP1255C3D 12-14 x 55mm SDHCP1265C3D 12-14 x 65mm SDHCP1272C3D 12-14 x 72mm






POLY-FAST™ Metal Polycarbonate Roof Fasteners

Fixing Polycarbonate Skylight to Steel

ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max 4.5mm thick

PRODUCT FEATURES


Hex Washer Flange Head Integrated Depth Stop Knurls 11mm Expansion Hole Cutter Thunder Shot Self-Drilling Point




Domed, Weatherseal, Anti-static EPDM Washer









Product Code

BN4-SDXPS1260C4

Specification

#12-14 x 60mm

Corrosion Resistance

True Australian Standard Class 4 Coating (C4)

Installation Procedure



Saves 50% of labor time, create a perfectly round expansion hole, and fix sheets in one go.



The Expansion Hole Cutter works in combination with the Depth Stop Knurls, and prevents overdriving of the screw after touching the purlin.



A perfectly round nominal 11mm diameter hole is created by theThermal Expansion Hole Cutter during the process.



A large Domed Weatherseal EPDM washer with two concentric sealing rims on the washer underside completes the package.




POLY-FAST™ Timber Polycarbonate Roof Fasteners

Fixing Polycarbonate Skylight to Timber

ADAPTER TO USE

Magnetic Hex Socket (5/16")



TIMBER PENETRATION

Min 25mm penetration

PRODUCT FEATURES


Hex Washer Flange Head Integrated Depth Stop Knurls 11mm Expansion Hole Cutter Type 17 Needle Point



Domed, Weatherseal, Anti-static EPDM Washer







11mm Expansion Hole Cutter

Hex Washer Flange Head

Coarse Thread

Integrated Depth Stop Knurls

Domed Weatherseal EPDM washer

Type 17 Needle Point

Product Code

BN4-T17HXPS1250C4

Specification

#12-11 x 50mm

Corrosion Resistance

True Australian Standard Class 4 Coating (C4)

Installation Procedure



Saves 50% of labor time, create a perfectly round expansion hole, and fix sheets in one go.



The Expansion Hole Cutter works in combination with the Depth Stop Knurls, and prevents overdriving of the screw after touching the purlin.



A perfectly round nominal 11mm diameter hole is created by theThermal Expansion Hole Cutter during the process.



A large Domed Weatherseal EPDM washer with two concentric sealing rims on the washer underside completes the package.




POLY-FAST™ Duo Polycarbonate Roof Fasteners

Dual purpose, Fixing Polycarbonate Skylight to Metal and Timber

ADAPTER TO USE

Magnetic Hex Socket (5/16")



STEEL PENETRATION

Max. 3.0mm thick

PRODUCT FEATURES


Hex Washer Flange Head Integrated Depth Stop Knurls 11mm Expansion Hole Cutter Dual purpose Duofix V-Drill




Domed, Weatherseal, Anti-static EPDM Washer









Product Code

BN3-S17HXPS1250C3

Specification

#12-11 x 50mm

Corrosion Resistance


True Australian Standard Class 3 Coating (C3)



Collated Drywall Screw



Collated Bulge Head Screws for Thin Steel



Fine Thread


Dimension

M3.5 x 25mm #6-18 x 1"
M3.5 x 32mm #6-18 x 1-1/4"

M3.5 x 41mm #6-18 x 1-5/8"



Collated Bulge Head Screws for Timber



Coarse Thread

Dimension

M3.5 x 25mm #6-9 x 1"


M3.5 x 32mm #6-9 x 1-1/4"

M3.5 x 41mm #6-9 x 1-5/8"



Standard Packaging:

50pcs/strip, 1000pcs/box and 10000pcs/ctn



Inner Box

Size: 560 x 120 x 50mm




Outer Box

Size: 573 x 255 x 283mm




BN3 TIMBER-Tite™ Self-Tapping Screws (Type 17)

Fixing roof sheeting to timber - Valley Fixing Fasteners



ADAPTER TO USE

Magnetic Hex Socket (5/16")



TIMBER PENETRATION

Min. 20mm penetration


PRODUCT FEATURES

Hex Washer Flange Type 17 Sharp Point

WASHER

Eco-BDN® Green Washer





PART NUMBER


#10 Gauge


T17H1020C3N 10-12 x 20mm



BN3 TIMBER-Tite™ Self-Tapping Screws (Type 17)


Fixing roof sheeting to timber - Crest Fixing Fasteners





ADAPTER TO USE

Magnetic Hex Socket (5/16")



TIMBER PENETRATION

Min. 25mm penetration

PRODUCT FEATURES

Hex Washer Flange Type 17 Sharp Point Double Thread Scratshank

WASHER

Eco-BDN® Green Washer





PART NUMBER

#12 Gauge

T17HCG1250C3N 12-11 x 50mm T17HCG1265C3N 12-11 x 65mm T17HCG1275C3N 12-11 x 75mm

Quality Assurance



To show our commitment to being a trustworthy supplier, and provide the best product and services, **BDN Fasteners**® are manufactured and quality controlled following ISO standards, and is of course, ISO-9001:2015 certified. EN 14566 certificate.







SGS Certification

BDN Fasteners BN3 Series screws are regularly sent to SGS for Kesternich & Spray Salt Test (1000 hrs) certification.

As part of our new quality assurance policy, which aims to provide high quality, third-party laboratory certified products — customers will now receive the most up-to-date corrosion resistance certifications upon request.



QUALITY CONTROL IN PROCESS



PRE-PRODUCTION INSPECTION

Drawing Check Specific Conditions Check

HEADING / THREADING / PINCH POINTING

Machinery Condition Check

Molds and Dies Inspection and Setup

HEAT TREATMENT

Strictly controlled process
Fully equipped with well maintained case depth and hardness testers

SURFACE TREATMENT

Well equipped with salt-spray and corrosion test machinery

PRE-SHIPMENT INSPECTION

Manual Sorting and Rearrangement Optical Sorting (Optional)

FINAL INSPECTION

Dimensions Functionality Aesthetics

PRE-SHIPMENT SAMPLES SENT UPON REQUEST









Product Guides and Tips



Screw Description



Screw Installation





Packaging Guide



Brand new packaging, upsized logos, spiced up head markings and more! Updated color scheme means you'll never have trouble spotting trusty **BDN Fasteners**® anymore!



Product Label


BDN Fasteners® come with large, easy to read product labels. Each product has its own unique label showing the product category, packaged quantities, size, part no., color, and description.

To re-order, use the Part No., Product Description, and Color Code as indicated below. This information can be easily obtained from any of our existing packaging.






All **BDN Fasteners**® product labels must be placed at the designated area on the carton as stated below.




Size: 140 x 80 mm





BDN Fasteners® product labels are always placed at the center of the box.







HEADQUARTER - TAIWAN

No. 47-37, Jiahua Rd., Gangshan, Kaohsiung 820, Taiwan (R.O.C.)

T +886 7-6282702 | F +886 7-6282601 | E info@bdnfasteners.com

www.bdnfasteners.com